imagePROGRAF TM-5250 | TM-5255



# **JustPerfect.** Limitless Creativity Made Possible



The new 24" **imagePROGRAF TM-5255** and **TM-5250** large format printers raise the standard for print excellence through greater business printing performance for creating photo images, posters and CAD drawings. Express limitless creativity through vivid, quality prints thanks to improved ink capabilities.

# High-Quality Printing For Everything Creative

Create vivid, high-quality photos and posters with the new 24" **imagePROGRAF TM-5255** and **TM-5250** large format printers. The improved ink capabilities help to bring out greater colour expressions within prints, while catering to the needs of engineering firms by offering multi-application printing suited for limitless creativity.





# Greater Productivity with Swiftness

Experience enhanced printing productivity with the new L-COA PRO II high-speed imaging processing chip, which provides greater data processing power that ensures quicker turnaround times from sleep mode alongside continuous printing with ease.

#### About 20% faster\*

\* Based on Canon internal testing using plain paper with continuous printing of A1 page per min

## **Print Borderless**

The **TM-5250** and **TM-5255** allow for **borderless poster printing** on any size of roll paper with ease.

### Vivid Red for Greater Details

The **new magenta ink** offers a more vivid red that enhances the details on printed photo images, posters and CAD drawings produced by the printer.



TM-5250

## **Designed for Convenience**

The printer's **flat top space** allows for effortless roll paper replacement or the placement of output prints.



Roll paper balance and paper media details can also be easily retrieved from the printer through **automatic paper type detection**.



# Improved Scanning for Productivity

The printers can be used alongside a scanner that features new functions, such as a **maximum paper thickness of 0.8mm** alongside **brand new transparent guides** that enhance scanning productivity and operability overall.



TM-5250 MFP Lm24

### **Managing Workflows with Ease**

Streamline how you manage workflows with convenient and intuitive software applications.

### **Direct Print Plus**

Direct Print Plus offers **easy batch printing of PDF and JPEG files** with custom templates.



#### **Accounting Manager**

The Accounting Manager feature offers greater convenience in **monitoring print usage**.



### **Free Layout Plus**

Free Layout Plus provides for **easy document resizing to specific paper layouts** before printing by simply dragging and dropping files into the application.



### **PosterArtist**

Design and **create visually appealing posters** effortlessly using the PosterArtist feature.

Check it out at https://posterartist.canon



### **SPECIFICATIONS**

Printer Type		TM-5250	TM-5255	
пппентуре		5-Colo	ur, 24"	
Number of Nozzles		15,360 nozzles (MBK 5,120 nozzles, Other Colours 2,560 nozzles each)		
Max. Print Resolution		2,400 x 1,200 dpi		
Nozzle Pitch		1,200 dpi × 2		
Line Accuracy <sup>*1</sup>		± 0.1 % or less		
Sales Ink		130 ml / 300 ml (MBK, BK, C, M, Y)		
Ink Tank Size	Bundle Starter Ink	130 ml (MBK) / 90 ml (BK, C, M, Y)		
Ink Type		Pigment Ink		
Print Languages		SG Raster (Swift Graphic Raster) HP-GL/2, HP RTL		
		JPEG (Ver. JFIF1.02) CALS G42		
		N/A	PDF	
Print Solutions & Applications		Printer Driver (Win/Mac versions), Direct Print Plus, Free Layout PLUS, PosterAritist Windows Web & Lite, Wi-Fi Connection Assistant, PIXMA Cloud Link, Apple AirPrint (Mobile), Canon PRINT Intget/SELPHY (Mobile), Canon Print System (Mobile), uniFlow server		
Management Solutions		Media Configuration Tool (includes Color Customisation Tool), Accounting Manager, Device Management Console, Quick Utility Toolbox		
	USB B Port	Hi-Speed USB, Full Speed (12 Mbit/sec), Hi-Speed (140 Mbit/sec), Bulk Transfer, Series B (4 pins)		
Interface (Built-In)	USB A Port	N/A	USB Memory (Direct Print) Supported file format: JPEG/PDF	
	Network	IEEE 802.3 10base-T IEEE 802.3u 100base-TX IEEE 802.3a 1000base-TX IEEE 802.34 Full Doublex SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP		
	Wireless LAN	IEEE802.11 b/g/n WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES) WPA3-SAE (AES) WPA-EAP (AES) <sup>13</sup> WPA2-EAP (AES) <sup>13</sup> WPA3-EAP (AES) <sup>13</sup>		
Memory Hard Disk		2 GB No Hard Disk	128 GB (Physical Memory 2 GB) 500 GB (Encrypted) Hard disk	
Display		LCD (4.3 inch / 10	I ).9 cm TFT color)	
	Please visit https://asia. canon to	Windows, Macintosh		
OS Compatability	confirm OS compatibility and to download the latest drivers.	Windows, I	Macintosh	
	confirm OS compatibility and to download the	Windows, I	Macintosh	
SCANNER	confirm OS compatibility and to download the	Windows, I Lm24	Macintosh	
SCANNER Scanner Model Scan Width	confirm OS compatibility and to download the latest drivers.	Lm24 24*	Macintosh	
SCANNER Scanner Model Scan Width	confirm OS compatibility and to download the latest drivers.	Lm24 24" Up to 600 dpi	Macintosh	
SCANNER Scanner Model Scan Width Optical Resolution	confirm OS compatibility and to download the latest drivers.	Lm24 24*	Macintosh	
Scanner Model Scan Width Optical Resolutior Scan Format	confirm OS compatibility and to download the latest drivers.	Lm24 24* Up to 600 dpi TIFF, TIFF G4, PDF/A, JPEG	Macintosh	
SCANNER Scanner Model Scan Width Optical Resolutior Scan Format	confirm OS compatibility and to download the latest drivers. n (DPI)	Lm24 24" Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG	Macintosh	
SCANNER Scanner Model Scan Width Optical Resolution Scan Format Scan Destinations Scanner Software Max. Copy Speed:	confirm OS compatibility and to download the latest drivers.	Lm24   24*   Up to 600 dpi   TIFF, TIFF G4,   PDF, PDF/A, J/EG   Multipage PDF & J/PEG   Scan to PC, USB   ScanAPP   Colour   Draft (300/300 dpi):   1 ips / 25.4 mm per sec   Standard (300/600 dpi):   1 ips / 25.4 mm per sec   Best (600/600 dpi):   0.5 ips / 12.7 mm per sec	Macintosh	
SCANNER Scanner Model Scan Width Optical Resolution Scan Format Scan Destinations Scanner Software Max. Copy Speed:	confirm OS compatibility and to download the latest drivers.	Lm24 24* Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, I/PEG Multipage PDF & I/PEG Scan to PC, USB ScanAPP Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Standard (300/600 dpi): 0.5 ips / 12.7 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Standard (300/300 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 3 ips / 76.3 mm per sec Best (600/600 dpi): 3 ips / 78.3 mm per sec Best (600/600 dpi): 3 ips / 78.3 mm per sec	Macintosh	
SCANNER Scanner Model Scan Width Optical Resolution Scan Format Scan Destinations Scanner Software Max. Copy Speed: (inch/sec) or (mm,	confirm OS compatibility and to download the latest drivers.	Lm24 24* Up to 600 dpi TIFF, TIFF G4, PDF, PDF/A, IPEG Multipage PDF & IPEG Scan to PC, USB Scan APP Colour Draft (300/300 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300/600 dpi): 1.5 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 0.5 ips / 12.8 mm per sec Best (600 dpi): 0.5 ips / 1		
SCANNER Scanner Model Scan Width Optical Resolution Scan Format Scan Destinations	confirm OS compatibility and to download the latest drivers. (DPI) (DPI) (Sec)	Lm24 24* Up to 600 dpi TIFF. TIFF. G4, PDF, PDFA, IPEG Multipage PDF & IPEG Scan to PC, USB Scan APP Colour Draft (300/800 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 0.5 ips / 12.7 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec Standard (300 dpi): 1 ips / 25.4 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec Best (600 dpi): 1 ips / 25.4 mm per sec		

PRINT SPEED <sup>14</sup>		TM-5250	TM-5255		
Plain Paper	CAD Drawing (A1 Portrait, Fast Q5 mode)	20 sec			
Heavyweight Coated Paper	Poster (A1 Portrait, Standard mode)	1 min 23 sec			
MEDIA HANDLING	a				
	Roll Paper	203.2 ~ 610 mm			
Media Width	Cut Sheet				
Media Thickness	Roll Paper/ Cut Sheet	0.07 ~ 0.8 mm			
Deinstehle Mardia	Roll Paper	203.2 mm ~ 18 m*5			
Printable Media Length	Cut Sheet	279.4 ~ 1,600 mm			
Media Core Size		2 inch / 3 inch core			
Outside Diameter Roll Paper		150 mm or less			
	Roll Paper	1 Roll, Top Load, Front Output			
Media Feed	Cut Sheet				
Delivery Direction	ouroneer	Front Load, Front Output			
Delivery Direction		Face-up, Front side			
Margins (Top, Bottom, Side)	Recommended Area (Roll Paper)	20 mm, 3 mm, 3 mm			
	Recommended Area (Cut Sheet)	20 mm, 20 mm, 3 mm			
	Printable Area (Roll Paper)	3 mm, 3 mm, 3 mm			
	Printable Area (Roll Paper Borderless Print)	0 mm			
	Printable Area (Cut Sheet)	3 mm, 20 mm, 3 mm			
DIMENSIONS (Wx	DxH) & WEIGHT*6				
Packaged Dimensions & Weight	Printer (Main unit + Pallet)	1,152 x 913 x 679 mm Weight: 73 kg			
	Stand + Basket (SD-26)	1,058 x 826 x 270 mm Weight: 22 kg			
	Printer (Main unit with stand and pallet) (SD-26)	1,152 x 913 x 946 mm Weight: 96 kg			
	Printer	978 x 748 x 439 mm (Operation panel is not tilt up) Weight: 42 kg (excluding print head and ink)			
Printer & Weight	Printer with Stand + Basket (SD-26)	978 x 885 x 1,060 mm (Basket Opened) 982 x 756 x 1,060 mm (Basket Closed) Weight: 55 kg (excluding print head and ink)			
Scanner & Weight		935 x 253 x 131 mm Weight: 5.28 kg	N/A		
POWER AND ORE	RATING REQUIRE				
POWER AND OPERATING REQUIRE Power Supply (Printer)		AC 100 - 240 V (50 - 60 Hz)			
Power Consumption (Printer)	Print Operation	Operation: < 62 W	Operation: < 64 W		
	Sleep Mode	<1.6 W			
	Power OFF	< 0.1 W			
Recommended	Temperature	Temperature: 15 - 30 °C			
Environment	Humidity	Humidity: 10 - 80 % RH (no dew condensation)			
	Power*7	Approx.			
Acoustic	Pressure*7	Approx. 41 dB(A), Standby 35 dB(A) or less			
OPTIONAL ACCESSORIES					
Roll Unit		-			
2/3" Roll Holder		RH2-28			
Printer Stand + Basket		SD-26			
Card Reader Interface for uniFLOW CONSUMABLES		RA-02			
Ink Tank		Magenta: PFI-8121 (130 ml) / PFI-8321 (300 ml) Matte Black / Black / Cyan / Yellow: PFI-8120 (130 ml) / PFI-8320 (300 ml)			
Print Head		-			
Cutter Blade		PF-06 CT-08			
Maintenance Cartridge		MC-31			
Internetional Constituye					
Specifications are subject to change without notice.					

<sup>11</sup> User adjustments required. Printing environment and media must match those used for the adjustments. Paper required: Plain paper and coated paper only.

\*2 USB Thumb drive printing is not supported.

\*3 IEEE802.1X (EAP-TLS/EAP-TTLS/PEAP) Supported.

<sup>54</sup> Time taken to print one page does not include time required for data processing, data transfer and pre-printing operations.

 $^{\ast_{5}}$  Varies according to the OS and application.

\*6 Include roll holder set.

 $^{\ast 7}$  Acoustic Power and Pressure are measured using ISO 7779 standard.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

Delighting You Always

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel : 65-6799-8888 | Fax : 65-6799-8882 | https://asia.canon

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.