



Wireless Refillable Ink Tank Printer with Fax for Low-Cost Printing

Enjoy the convenience of wireless printing and high-productivity with the PIXMA G4770. This 4-in-1 printer features a 35-sheet Auto Document Feeder for batch scanning productivity.









EASY, HASSLE-FREE INK REFILL

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.



EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.



AUTO DOCUMENT FEEDER

Up to 35 sheets of document originals can be loaded for batch scanning and copying, eliminating the need for repeated opening and closing of the scanner lid



MOBILE AND CLOUD PRINTING

Print from smartphones, tablets, laptops and cloud storage with the Canon PRINT Inkjet/SELPHY and Easy-PhotoPrint Editor apps.



SPE	CIFICATIONS			PIXMA G4770
	Maximum Printing Resolution			4,800 (horizontal) ^{*1} x 1,200 (vertical) dpi
PRINT		ESAT/Simplex (Mono/Colour)		11 / 6 ipm
	Print Speed*2	FPOT Ready/Simplex (Mono/Colour)		9 / 14 sec
		Photo (4 x 6")		45 sec
SCAN'3	Scanner Type			Flatbed (ADF / Platen)
	Scanning Method			Contact Image Sensor (CIS)
	Optical Resolution' ⁴			600 x 1,200 dpi
	Flatbed			A4, LTR (216 x 297 mm)
	Maximum Document Size ADF			A4, LTR, LGL
COPY	Copy Speed' ⁵	Colour	sFCOT/Simplex	23 sec
			sESAT/Simplex	3.2 ipm
		ADF (Colour)	ESAT/Simplex	1.8 ipm
	Maximum Copies			99 pages
	Maximum Document Size			A4, LTR
	Transmission Speed ^{'6} Mono/Colour			3 sec / 1 min
FAX	Transmission/Reception Memory ^{'7}			50 pages
	PC Fax			Windows: Available, Mac: Available
	Automatic Dialing Coded Speed Dialing (max.)		Pialing (max.)	20 locations
	Automatic Dialing	Group Dialing (19 locations
	Maximum Input Capacity	Rear Tray	Plain Paper (64 g/m²)	Up to 100 sheets
PAPER HANDLING			Photo Paper (4 x 6")	Up to 20 sheets
		ADF	Plain Paper (64 g/m²)	A4, LTR: 35 sheets, LGL: 5 sheets
	Media Size	Rear Tray		A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1,200 mm)
	Media Type	Rear Tray		Plain Paper (64 – 105 g/m²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208, PS-808) Envelope
NETWORK SYSTEM REQUIREMENTS & General Specifications	Operating System Compatibility	Please visit https://asia.canon to confirm OS compatibility and to download the latest drivers.		Windows 11 / 10 / 8.1 / 7 SP1" ⁸ macOS 10.14.16 – 12 or later Chrome OS
	Interface			Wireless LAN IEEE802.11b/g/n/a ⁻⁹ /ac ⁻⁹ USB 2.0
	Conon Brinting Anna	Mobile		Canon PRINT Inkjet/SELPHY, Easy-PhotoPrint Editor, Creative Park
	Canon Printing Apps	Others		Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect
	Mobile/Cloud Printing Solutions			AirPrint, Mopria, Canon Print Service (Android), Direct Wireless PIXMA Cloud Link
	Power			AC 100 – 240 V, 50/60 Hz
	Power Consumption ^{™0}			15 W (Standby: 0.6 W)
	Duty Cycle			Up to 3,000 pages/month
	Recommended Monthly Print Volume			150 – 1,500 pages
	Operation Panel Display			1.35" / 3.4 cm LCD (Monochrome)
	Dimensions (W x D x H)	Factory Configuration		416 x 337 x 212 mm
	Output/ADF Trays Extended			416 x 556 x 268 mm
	Weight			7.2 kg
CONSUMABLES	Ink Bottles	Type/Colours		Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow
	Page Yield** (A4, Pages)		4, Pages)	GI-7I PGBK: 6,000 (Standard) / 7,600 (Economy ⁻¹³) GI-71 C, M, Y: 7,700 ⁻¹² (Standard) / 8,100 ⁻¹² (Economy ⁻¹³)
8	User Replaceable Maintenance Cartridge			MC-G04

Specifications are subject to change without notice.

- 1 Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- ^{*a} TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available only when you use TWAIN Driver.
- Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
- *Black & white document fax transmission speed is based on default setting using ITU-T No. 1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No. 1.
- *8 Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
- ⁹ Wireless LAN IEEE802.11a/ac are available for Taiwan models only.
- *10 When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the Standard ink bottles after initial setup. Page yield varies significantly depending on contents printed and other factors.
- *12 Based on 1 set of colour bottles
- *19 The Economy mode reduces the ink consumption by lowering the density. More pages can be printed by using this mode.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel: 65-6799-8888 | Fax: 65-6799-8882 | https://asia.canon

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.