




Compact Wireless Photo All-In-One with Touchscreen LCD











AUTO DUPLEX PRINTING

Enjoy heightened productivity and ease-of-use by printing on both sides of papers automatically.



2-WAY PAPER FEEDING

Paper can be loaded for printing in 2 directions, via front cassette and rear feeding, eliminating the need to remove paper stacks and reloading.



MOBILE AND CLOUD PRINTING

With the Canon PRINT mobile app for iOS and Android OS, you can print documents stored in local device memory, or cloud storage.





SPECIFICATIONS / PIXMA TS7770								
PRINT	Maximum Printing Resolution*1			1,200 (horizontal) x 1,200 (vertical) dpi				
	Print Speed*2	ESAT/Simplex (Mono/Colour)		15 / 10 ipm				
		FPOT Ready/Simplex (Mono/Colour)		9 / 11 sec				
		Photo (4 x 6")		19 sec				
	Auto 2-Sided Printing			Yes				
SCAN*3	Scanner Type			Flatbed				
	Scanner Technology			Contact Image Sensor (CIS)				
	Optical Resolution*4			1,200 x 2,400 dpi				
	Maximum Document Size			A4, LTR (216 x 297 mm)				
СОРУ	Copy Speed'5	Colour	sFCOT/ Simplex	18 sec				
			sESAT/ Simplex	7 ipm				
	Maximum Copies			99 pages				
	Maximum Document Size			A4, LTR				
PAPER HANDLING	Maximum Input Capacity	Rear Tray	Plain Paper	Up to 100 sheets				
			Photo Paper (4 x 6")	Up to 20 sheets				
		Cassette	Plain Paper	Up to 100 sheets				
	Media Size	Rear Tray		A4, A4 Art Paper, A5, B5, LTR, LTR Art Paper, LGL, Envelope (COM10, DL), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Custom (width: 55 - 215.9 mm, length: 89 - 1,200 mm)				
		Cassette		A5, A4, B5, LTR				
		Borderless Printing ^{*6}		A4, B5, LTR, 4 x 6", 5 x 7", 8 x 10", Card Size (91 x 55 mm), Square (89 x 89 mm, 127 x 127 mm)				
	Media Type	Rear Tray		Plain Paper (64 - 105 g/m²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Paper Pro Platinum (PT-101) Premium Fine Art Rough (FA-RG1) Photo Stickers (PS-208/PS-808) Envelope				
		Cassette		Plain Paper (64 - 105 g/m²)				

${\bf Specifications\ are\ subject\ to\ change\ without\ notice.}$

- *1 $\,$ Ink droplets can be placed with a pitch of 1/1200 inch at minimum.
- *2 Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.

Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility	Please visit https://asia. canon/support to confirm OS compatibility and to download the latest drivers.		Windows 11 / 10 / 8.1 / 7 SP1* ⁷ , macOS 10.15.7 ~ 13 or later, Chrome OS
	Connectivity	Network		Wireless LAN IEEE802.11b/g/n
		Interface		USB 2.0
	Canon Printing Apps	Mobile		Canon PRINT, Easy-PhotoPrint Editor, Creative Park
		Others		Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect
	Mobile/Cloud Printing Solutions			AirPrint, Mopria, Canon Print Service (Android), Direct Wireless, Cloud Link
	Power			AC 100 - 240 V, 50/60 Hz
Σ	Power Consumption ¹⁸			21 W (Standby: 0.9 W)
NETWORK SYSTE	Recommended Monthly Print Volume			80 – 300 pages
	Operation Panel	Display		2.7" LCD (Touchscreen, Colour)
	Dimensions (WxDxH)			374 x 350 x 168 mm
	Weight			6.3 kg
CONSUMABLES	Ink Cartridges	Type/Colours		Pigment Ink / Black Dye-Based Ink / Colour
		Page Yield* ⁹	Plain Paper	A4 Colour Documents ⁻¹⁰ : Standard: PG-785: 180 / CL-786: 180 Optional: PG-785XL: 400 / CL-786XL: 400
			Photo Paper (PP-201)	4 x 6" Photos' ¹¹ ; Standard: PG-785: N/A / CL-786: 65 Optional: PG-785XL: N/A / CL-786XL: 146

- *3 TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- *4 Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available, only when you use TWAIN Driver.
- *5 Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
- *6 Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers.
- $^{*}7$ Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
- *8 When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- *9 Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.
- *10 Declared yield value is in accordance with ISO/IEC 24711, using the ISO/IEC 24712 colour chart. Values obtained by continuous printing.
- *11 Declared yield value is in accordance with ISO/IEC 29102, using the ISO/IEC 29103 chart. Values obtained by continuous printing. Black ink is not used when printing under this condition. However, a minimal amount of black ink is used for maintenance purposes.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel : 65-6799-8888 | Fax : 65-6799-8882 | https://asia.canon

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.