

PIXMA MG2570S

All-In-One Printer



ISO Standard Speed

approx. 8.0 ipm Black	approx. 4.0 ipm Colour
Print	

approx. 31 sec Colour	approx. 1.6 ipm Colour
Copy	

Measured by ISO/IEC 24734, 29183 standards



PIXMA iP2870S

Single-Function Printer



ISO Standard Speed

approx. 8.0 ipm Black	approx. 4.0 ipm Colour
Print	

Measured by ISO/IEC 24734 standards



Ink Cartridge Compatibility

LOW COST CARTRIDGES



For Occasional
Printing

745 Black
746 Color

745 Black XL
746 Color XL

Optional

For Everyday
Printing

For High-Volume
Printing

SPECIFICATIONS

			PIXMA MG2570S	PIXMA iP2870S		
Print	Maximum Printing Resolution*1		4800 x 600 dpi	4800 x 600 dpi		
	Number of Ink Cartridges		2	2		
	Print Speed*2	Document: B&W / Colour	ESAT / Simplex	approx. 8.0 ipm / 4.0 ipm	approx. 8.0 ipm / 4.0 ipm	
	Standard Paper Input (Front Cassette / Tray)	Plain Paper (Sheets)		A4 / A5 / B5 / Letter = 60 / Legal = 10 (Rear Tray)	A4 / A5 / B5 / Letter = 60 / Legal = 10 (Rear Tray)	
Scan	Scanner Type / Scanning Method		Flatbed / CIS (Contact Image Sensor)	NA		
	Optical Resolution*3		600 x 1200 dpi	NA		
	Scanning Speed*4	Reflective	A4 Colour / 300dpi	approx. 14 sec.	NA	
Copy	Maximum Document Size		A4 / Letter (216 x 297 mm)*5	NA		
	Copy Speed*6	Document: Colour	sFCOT / Simplex	approx. 31 sec.	NA	
			sESAT / Simplex	approx. 1.6 ipm	NA	
	Mutiple Copy	Black / Colour		1-21 pages	NA	
System Requirements & General Specifications	Windows	(Please visit www.canon-asia.com to confirm OS compatibility and to download the latest driver updates)		Windows 8 / Windows 7 / Windows Vista / Windows XP	Windows 8 / Windows 7 / Windows Vista / Windows XP	
	Macintosh			Mac OS X v10.7.5 and later	Mac OS X v10.7.5 and later	
	Interface				USB 2.0 Hi-Speed	USB 2.0 Hi-Speed
	Power Consumption				approx. 9W (1.0W Standby)	approx. 8W (0.8W Standby)
	Dimensions (W x D x H)				approx. 426 x 306 x 145 mm	approx. 426 x 235 x 134 mm
	Weight				approx. 3.5 kg	approx. 2.3 kg
	Page Yield	Plain Paper A4 (ISO / IEC 24712 test file)*7 (Pages)		PG-745S: 100 CL-746S: 100	PG-745S: 100 CL-746S: 100	
		Optional: PG-745: 180 CL-746: 180	Optional: PG-745: 180 CL-746: 180			
		Optional: PG-745XL: 300 CL-746XL: 300	Optional: PG-745XL: 300 CL-746XL: 300			

Specifications are subject to change without notice.

*1 Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

*2 Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO / IEC 24734. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used, etc.

*3 Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

*4 Colour document scan speed is measured with ISO / IEC 29183 Target A. Scan speed indicates the time measured between pressing the scan button of the scanner driver and the on-screen status display turning off. Scan speed may vary depending on system configuration, interface, software, scan mode settings, document size, etc.

*5 Document Size: Max. copy area of 203.2 x 277.3mm (with 16.7mm bottom print margin).

*6 Copy speeds are the average of sFCOT and sESAT, ISO / IEC 29183. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm-up time.

*7 Declared yield value in accordance with ISO / IEC 24711 (for A4 size) using ISO / IEC 24712 test file. Values obtained by continuous printing.

Note: All printers work in Operating Environment of Temperature: 5 - 35°C;

Humidity: 10 - 90% RH (no dew condensation).

All printers work in Storage Environment of Temperature: 0 - 40°C;

Humidity: 5 - 95% RH (no dew condensation).

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS:

CANON SINGAPORE PTE. LTD.

1 HarbourFront Avenue #04-01 Keppel Bay Tower Singapore 098632

Tel: 65-6799 8888 Fax: 65-6799 8882

www.canon-asia.com



www.facebook.com/CanonPIXMA