



Built for **Business**

High-Speed, Robust A3 Scanner for Businesses

Engineered for high-volume mixed batch scanning, the imageFORMULA DR-M1060II simplifies your business' document digitisation processes. Featuring full-front operation with the U-turn path mode, you can confidently and efficiently scan all that your business needs.

UP TO
60 PPM | 120 IPM*
FAST SCAN SPEED

*300 dpi, Greyscale, A4



*With Folio scan,
Long Document mode

UP TO
600 DPI
SCAN OUTPUT
RESOLUTION



Compact Space-Saving Design

The U-turn path mode enables full-front operation, while saving space when the DR-M1060II is placed on countertops or tight spaces.



Fast and High-Quality Scanning

The DR-M1060II scanner offers both fast capture speeds and impressive image quality, enabling you to increase productivity and scan with confidence.



Versatile Media Handling

The scanner can handle media of a wide-range of textures and thicknesses, making it simple and quick to set up. With just a touch of a button, you can swiftly scan paper documents, receipts, IDs, and business cards.



SPECIFICATIONS / DR-M1060II

SCANNING		
Type		Desktop Sheet-Fed Scanner
Scanning Speed ^{*1}	Greyscale	200 dpi: 60 ppm (Simplex) / 120 ipm (Duplex) 300 dpi: 60 ppm (Simplex) / 120 ipm (Duplex)
	Colour	200 dpi: 60 ppm (Simplex) / 120 ipm (Duplex) 300 dpi: 40 ppm (Simplex) / 80 ipm (Duplex)
Scanning Element		Contact Image Sensor (CIS)
Light Source		LED
Scanning Side		Simplex / Duplex
Scanning Modes		Black and White, Error Diffusion, 256-level Greyscale, Advanced Text Enhancement, Advanced Text Enhancement II, 24-bit Colour
Scanning Features		Folio Scanning, Double Feed Release, 2D / Barcode
Optical Resolution (Max.)		600 dpi
Output Resolution ^{*2}		100, 150, 200, 240, 300, 400, 600 dpi
MEDIA HANDLING		
Document Size	Plain Paper	Width: 50.8 to 300 mm Length: 70 to 432 mm (Up to 3,000 mm long with Long Document mode)
	Business Card	Width: 50.8 to 55 mm Length: 85 to 91 mm
	Card (ISO Standard)	54 x 86 mm
Document Thickness and Weight	Plain Paper	U-turn Path (Page Separation): 27 to 128 g/m ² (0.04 to 0.15 mm) U-turn Path (Non-Separation): 27 to 164 g/m ² (0.04 to 0.2 mm) Straight Path: 27 to 255 g/m ² (0.04 to 0.3 mm)
	Business Card	128 to 380 g/m ² (0.15 to 0.45 mm) (Use the straight path and place vertically)
	Card	0.76 mm or less, 1.4 mm or less for the embossment (Use the straight path and place vertically)
Auto Document Feeder Capacity ^{*3}		80 sheets
CONNECTIVITY & SOFTWARE		
Interface		Hi-Speed USB 2.0
Software		ISIS / TWAIN / WIA Drivers, CaptureOnTouch
GENERAL		
Power Requirements		AC 100 - 240 V (50 / 60 Hz)
Power Consumption	Scanning (Max.)	32.5 W
	Sleep Mode	1.9 W
	With Power Switched OFF (Max.)	0.1 W
Operating Environment	Temperature	10 to 32.5°C
	Humidity	20 to 80% RH
Dimensions (W x D x H)	When Trays Are Closed	424 x 246 x 120 mm
	When Trays Are Opened	424 x 440 x 210 mm
Weight (Approx.)		6.1 kg (Without AC adapter)
CONSUMABLES & ACCESSORIES		
Options / Consumables		Exchange Roller Kit
Accessories		Flatbed Scanner Unit 102, Flatbed Scanner Unit 201

Specifications are subject to change without notice.

^{*1} Based on A4 landscape document size.

^{*2} Primary scan lines x secondary scan lines.

^{*3} Size: A3 or smaller (Same type document only), Paper Weight: 70 to 100 g/m², Temperature: 15 to 27.5°C, Humidity: 25 to 75% RH, Total Thickness: 10 mm or less.



**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.**

438A Alexandra Road, #06-10, Alexandra Technopark, Singapore 119967
Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.